



ClassCo

Model PSM585 Emergency Notification Device

Fast, effective, and accessible notification for

- Colleges and Universities (on-campus and off-campus locations)
- Government Agencies
- Military Installations
- Enterprise Communications
- Service providers offering residential emergency notification

The PSM585 Emergency Notification Device provides immediate emergency notification when an emergency message is issued by public safety personnel any time of day or night. The message is delivered using a combination of persistent alarms, audible announcement of the emergency message, flashing lights, and text display. The PSM585 provides positive acknowledgement that the message was received.

The PSM Emergency Notification Device can activate external alerts such as strobe lamps, shakers, and vibrating pagers, and can translate emergency messages into the preferred language of the recipient.

The PSM Emergency Notification Device provides rapid and effective notification for all citizens, including children, elderly, multilingual populations, first responders, and people with special needs.

Features

- Connects to both PSTN and IP/LAN/VOIP networks
- Persisting notification using alarms, audible message announcements, text, and lights
- Always on for immediate awareness of the emergency situation any time day or night
- Positive acknowledgement of message receipt
- 10X faster than telephone calls
- Eliminates bottlenecks and network delays inherent in EMAIL and SMS systems
- Accessible to people with special needs and multi-lingual communities
- Alarm output port to drive external devices (sirens, strobe lamps, vibra-alerts)
- Indoor and Outdoor applications
- Emergency Call Button (optional pendant)

Designed to Telcordia and NFPA standards

Operates in conjunction with ClassCo's PSM Messenger software application

CLASSCO

Model Number: PSM585 Emergency Notification Device

Physical Specifications

Unit Dimensions: 5-3/8" x 4-3/8" x 2"
Packaged Dimensions: 7-1/4" x 5-1/2" x 2-1/4"
Packaged Weight: 22 oz

Packaging

UPC: 616015 10033

Master Carton

Unit quantity per carton: 12
Carton Dimensions: 13-3/4" x 12-1/4" x 7-3/4"
Carton Weight: 16 lbs

Technical Specifications

Power input: 120VAC, Output 6VDC 400mA
Standby battery: 4 x AA
Standby duration: 72 hours under alarm condition
Network Port: PSTN RJ11 (IP/LAN/VOIP with ATA)
Telephone Port: PSTN RJ11
Aux Alarm: 2-position push terminal with dry contact closure
FCC/ACTA: 1XHKGND01A10033 REN0.1A
IC/DOC: 2560B-10033
Emissions: FCC Part 15B
Safety Listings: UL 60950-3, CSA C22.2, ETL Listing 2000095

Compliant with NFPA 1221 (2002)
Meets Telcordia PSTN-to-CPE Data Specifications TM26023, TM26028, and GR-30-CORE

Manufactured by:

ClassCo Inc.
99 Airport Road
Concord, NH 03302 USA

Tel 603-225-2990
Fax 603-225-2998
sales@classco.com

www.classco.com



ClassCo® and VoiceAnnounce® are registered trademarks of ClassCo Inc.
Copyright © ClassCo Inc. All rights reserved.
Printed in USA.